## Product selection



Use the chart below to select the most appropriate escape or working rescue breathing apparatus for your requirements:

	- ATTI	J. C. L.	- drew	SWA OFFIN	100 mm	
	HEAD10	HEAD15	HEAD30	HEAD15 Work Rescue	MARINE 15 EEBD	INDUSTRIAL 20 EEBD
Part No.	802.000.19	802.001.15	802.003.01	802.001.10	802.015.00	802.001.15
10 minute duration Escape	<b>✓</b>	<b>✓</b>	<b>✓</b>	Х	<b>✓</b>	<b>✓</b>
15 minute duration Escape	X	<b>✓</b>	<b>✓</b>	Х	<b>✓</b>	<b>✓</b>
20 minute duration Escape	X	Х	<b>✓</b>	Х	X	<b>✓</b>
30 minute duration Escape	X	Х	<b>✓</b>	Х	X	Х
15 min Working/Rescue	X	Х	Х	<b>✓</b>	X	Х
Chemical O2/instant start	<b>✓</b>	<b>~</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
No face fit test	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	✓	<b>✓</b>
Head worn with integral oro-nasal mask	~	~	~	~	X	×
Mouthpiece & nose clip	Х	Х	Х	Х	<b>✓</b>	<b>✓</b>
Hood/Face shield	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
Panoramic visor	✓	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
Audio visual safety alarm	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	Х	Х
Revalidation 6 & 9 years/ refurbishment	~	~	~	~	X	×
Voice communication once donned	~	~	~	~	X	×
Single use	X	Х	X	Х	<b>✓</b>	<b>✓</b>
Storage integrity indicator	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
Storage life up to 12 years	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
Storage life up to 15 years	X	X	X	X	<b>✓</b>	<b>✓</b>
UKCA & CE Approval	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
EN 13794	<b>✓</b>	✓	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
DIN 58639 & 58562-1	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	X	X
ISO23269-1:2008	X	X	X	X	<b>✓</b>	<b>✓</b>
PPE Regulation compliant	<b>✓</b>	<b>✓</b>	✓	<b>✓</b>	X	<b>✓</b>
MARINE Equipment Directive compliant	X	X	X	×	✓	X
MED Wheelmark (SOLAS)	X	X	X	X	<b>✓</b>	X